

Wooden Pallet CP8 (chemical standard)

Dimensions	
Length	1140 mm
Width	1140 mm
Height	156 mm
Weight (*)	40,55 kg

(*) Average value. Weight may vary following moisture content in the wood, specie of the wood. Valuation can reach 30% after kiln-dry.

Manutention	
Entries	4
Bottom boards	4
Rackable	Oui / Yes
Nestable	Non / No
Stackable	Oui / Yes
Forks entry height	98 mm
Forks entry Width	400 mm

Resistance	
Static loading weight max (*)	3400 kg
Dynamic loading weight max (*)	1500 kg
Footprint	1,30 m ²
Volume	,20 m ³
ISMP15 conformity	Oui / Yes
Kiln Dry	Non / No
Average moisture content (**)	45 %

(*) Following uniform conditioning and use as normal condition.

(**) Average moisture content, may vary following ambient hygrometry and/or storage conditions and/or date of production

Matière	
Raw material	Wood
Number of blocks	12
Raw material of blocks	Wood or composite

Composition (en mm)*					
	Quantité	Longueur	Largeur	Epaisseur	
Top Boards 1	3	1140	100	18	
Top Boards 2	6	1140	80	18	
Stringer 1	4	1140	80	22	
Stringers 2					
Blocks or Bars 1	8	100	80	80	
Blocks or Bars 2	4	100	80	80	
Bottom boards 1	4	1140	100	18	
Bottom boards 2	3	1140	100	18	
Chamfer	Oui / Yes				
Full Tray	0				
Corner Cut	Oui / Yes				
Overflowing Tray	Oui / Yes				
Space between boards	45,00				
Cubage Théorique (dm3)	46,08				

(*) Dimensions may vary of +/- 3 % par item following specie used and/or moisture content and/or storage time and/or storage condition.



Exportation :

Strongly recommended for your exportation: add a mechanical drying to the mandatory ISPM15 treatment.

This will prevent mold and/or mushrooms that may cause potentially cardboard and product contamination.