

## Wooden Pallet CP5 (chemical standard)

Dimensions	
Length	1140 mm
Width	760 mm
Height	138 mm
Weight (*)	25,37 kg

(\*) Average value. Weight may vary following moisture content in the wood, specie of the wood. Valuation can reach 30% after kiln-dry.

Manutention	
Entries	4
Bottom boards	3
Rackable	Non / No
Nestable	Non / No
Stackable	Oui / Yes
Forks entry height	98 mm
Forks entry Width	260 mm

Resistance	
Static loading weight max (*)	2790 kg
Dynamic loading weight max (*)	1066 kg
Footprint	,87 m <sup>2</sup>
Volume	,12 m <sup>3</sup>
ISMP15 conformity	Oui / Yes
Kiln Dry	Non / No
Average moisture content (**)	45 %

(\*) Following uniform conditioning and use as normal condition.

(\*\*) Average moisture content, may vary following ambient hygrometry and/or storage conditions and/or date of production

Matière	
Raw material	Wood
Number of blocks	9
Raw material of blocks	Wood or composite

Composition (en mm)*					
	Quantité	Longueur	Largeur	Epaisseur	
Top Boards 1	3	1140	100	18	
Top Boards 2	4	1140	80	18	
Stringer 1	3	760	100	22	
Stringers 2					
Blocks or Bars 1	9	0	0	80	
Blocks or Bars 2	0	0	0	0	
Bottom boards 1	2	1140	80	18	
Bottom boards 2	1	1140	100	18	
Chamfer	Oui / Yes				
Full Tray	Non / No				
Corner Cut	Oui / Yes				
Overflowing Tray	Non / No				
Space between boards	23,33				
Cubage Théorique (dm3)	28,83				

(\*) Dimensions may vary of +/- 3 % par item following specie used and/or moisture content and/or storage time and/or storage condition.



**Exportation :**

***Strongly recommended for your exportation: add a mechanical drying to the mandatory ISPM15 treatment.***

***This will prevent mold and/or mushrooms that may cause potentially cardboard and product contamination.***