

Wooden Pallet CP6 (chemical standard)

Dimensions	
Length	1200 mm
Width	1000 mm
Height	174 mm
Weight (*)	38,72 kg

(*) Average value. Weight may vary following moisture content in the wood, specie of the wood. Valuation can reach 30% after kiln-dry.

Manutention	
Entries	4
Bottom boards	6
Rackable	Oui / Yes
Nestable	Non / No
Stackable	Oui / Yes
Forks entry height	80 mm
Forks entry Width	330 mm

Resistance	
Static loading weight max (*)	3480 kg
Dynamic loading weight max (*)	2400 kg
Footprint	1,20 m ²
Volume	,21 m ³
ISMP15 conformity	Oui / Yes
Kiln Dry	Non / No
Average moisture content (**)	45 %

(*) Following uniform conditioning and use as normal condition.

(**) Average moisture content, may vary following ambient hygrometry and/or storage conditions and/or date of production

Matière	
Raw material	Wood
Number of blocks	9
Raw material of blocks	Wood or composite

www.mypalletsonline.com

Composition (en mm)*					
	Quantité	Longueur	Largeur	Epaisseur	
Top Boards 1	2	1200	120	18	
Top Boards 2	7	1200	80	18	
Stringer 1	3	1000	100	22	
Stringers 2					
Blocks or Bars 1	9	0	0	80	
Blocks or Bars 2	0	0	0	0	
Bottom boards 1	3	1100	80	36	
Bottom boards 2	3	900	100	18	
Chamfer	Oui / Yes				
Full Tray	Non / No				
Corner Cut	Oui / Yes				
Overflowing Tray	Oui / Yes				
Space between boards	25,00				
Cubage Théorique (dm3)	44,00				

(*) Dimensions may vary of +/- 3 % par item following specie used and/or moisture content and/or storage time and/or storage condition.



Exportation :

Strongly recommended for your exportation: add a mechanical drying to the mandatory ISPM15 treatment.

This will prevent mold and/or mushrooms that may cause potentially cardboard and product contamination.

www.mypalletsonline.com